




FA 60 029 XX

P. 1 | 2



HS CODE
63079098
CARTON SIZE / PCS.
FA 60 029 05 : 40 x 40 x 24 cm / 10
FA 60 029 10 : 60 x 40 x 24 cm / 20
AET (UE) N°2777_26029-01_E00-00
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 60 029 05 FA 60 029 10
CE	EN 795:2012 Type B
	x1
LG.	Max. 5 m Max. 10 m
MAT.	 45mm PES
R (kN) / MBS (kN)	18 kN / 19 kN
	0.61 kg 0.98 kg



Nombre d'utilisateurs
 Number of users
Cantidad de usuarios
 Quantità di utilizzatori
Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
 Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
 Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)