


BEL LIGHTING | Indy

Item code: **8066.1D1.02**

IK09

IP65


Class I



See more details accessories pages.
Voir plus de détails pages des accessoires.
Zie meer details accessoires pagina's.
Mehr Details auf den Zubehörseiten.

Pic 2

*do not use version rusty iron on tiling, paving, wood, ...



Product Description

INDY is a Led bollard that is particularly well-suited to ambient, boundary and guidance lighting thanks to its glare-free illumination. It is a quality product made from profile aluminium or rusty iron. Thanks to its design and the many colours and variants available, INDY will fit in perfectly along your pathways or in your gardens and parks, not only creating atmosphere but also adding a touch of originality and modernity.

General technical data

Manufacturing material :	Body made in aluminum
Surface finishing* :	Black
Diffuser type :	Clear plexiglas (transparent)
Fixation :	 ground
IP Protection degree :	IP65
Shock resistance degree :	IK09
Reference temperature :	25°C
Working Environment Temperature :	-20°C > +50°C
Minimum Life time @ Ta 40°C :	85.000hrs (L80 B10)
Weight (Kg) :	2.10 Kg
Dimensions mm (L x W x H):	150 x 60 x 600 mm
Country of origin :	made in Belgium**

Reference Standards and Directives

Warranty :	3 years extendable to 5
Product certification :	CE
Certification and approval marks :	ISO 9001 - 14001 - 45001

Available accessories

IP68 connection - Connex 2 / 4 / 6

Anti-ant gasket - ref: GK.100X080

Spike for ground fixing - Pic 2 ref: 803.00.02

Lighting characteristics

Number of light sources :	1
Light source type :	Led 9,5W 4000K
Luminaire power :	9.5 W
Colour temperature :	4000 K
Colour Rendering Index :	CRI>90
Luminous flux (lumens) :	1095 lm
Luminous flux efficiency :	115 lm/W
MacAdam step :	3
Beam angle ° FWHM :	100°
Lighting type :	direct
This product contains a lightsource of energyclass :	F

Electrical characteristics

Insulation Class :	Class I
Voltage / Current :	220-240V / 50-60Hz
Dimmable :	Dimmable on request

Available On Request

Other RAL colors or dimensions (customized)

Other led color: 2200K / 3000K / 5000K

Led 6W 2200K / 2700K / 3000K / 4000K / 5000K

Dimmable power supply 220-240V

Power supply 24VDC included

* Please refer to the information pages for the specific characteristics of anodized surfaces.

** All light fixtures shipped from our address in Megara, Greece are made in Greece.

BEL LIGHTING | Indy

Item code: **8066.1D1.02**

IK09

IP65

Class I



Others photos
from the same range

